



## Hydraulische Stangenlagerung! Schnelles Beladen! Hohe Produktivität!

Einfache und schnelle Umrüstung. Zusätzlich manuelles Steuergerät für eine einfache Einrichtung.



	Г					
N4 - O -	L	Α	В	В	<u> </u>	Weight
Maße 3870 mr		3200 mm	1810 mm		2 mm	520 kg
			B L	•	900 - 1200	28 367
Modell		12	16	20	23	26
Stangendurchmess	er	Ø 3 - 12 mm	Ø 3 - 16 mm	Ø 3 - 20 mm	Ø 3 - 23 mm	Ø 5 - 26 mm
		(1/8" - 1/2")	(1/8" - 5/8")	(1/8" - 25/32")	(1/8" - 7/8")	(3/16" - 1")
		Ø 4 - 11 mm	Ø 4 - 14 mm	Ø 4 - 17 mm	Ø 4 - 19 mm	Ø 4 - 21 mm
		(3/16" - 7/16")	(3/16" - 9/16")	(3/16" - 11/16	(3/4" - 13/16")	(3/16" - 13/16")
Kanaldurchmesser		14	18	22	24	28
Ladekapazität		260 mm Ø10 mm x 26 pcs.				
Druckluft		5 - 7 kg/cm2				
Stromversorgung		3Phase 200 ~ 240 VAC 5 A 50/60 Hz				



SAMSYS GmbH

Obere Schanzenstr. 1-7 | 55232 Alzey / GERMANY

Tel.: +49 (0) 6731 / 99 89 95-0 | Fax: +49 (0) 6731 / 54 87 96 4

E-Mail: contact@samsys.eu | www.samsys.eu